

## Performance/ Performances/ Prestaciones

- Maximum sand quantity in the water/ Max quantite de sable dans l'eau/  
Maxima cantidad de arena en el agua - 200 g/m<sup>3</sup>
- Water temperature up to/ Temperature de l'eau jusqu' a/ Temperature del agua hasta - 60 degree Celcius
  - Connection/ Connexion/ Acoplamiento - NEMA Standards
  - Impeller/ Roues/ Rodete - mixed flow/ helicocentrifuges/ semi axiales
- Installation/ Instalacion - horizontal and vertical/ horizontale and verticale

Type Tipo	N. Stages N. Etage N. Etapas	Motor/ Moteur			Pump/ Pompes/ Bombas				Q m <sup>3</sup> /h l/min	Delivery/ Debit/ Caudal								
		Type Tipo	KW	HP	A (mm)	DN (RPT or NPT)	B (mm)	Kg		0	5	10	15	20	25	30	35	40
WSP630-3	3	4"	4.00	5.50	512	3"	136	13.0	Head/ Hauteurman/ Alturaman H m	34.4	34.0	33.0	31.3	29.1	26.4	23.0	19.0	14.5
WSP630-4	4	4"	4.00	5.50	595	3"	136	15.5		45.9	44.9	43.3	40.9	37.9	34.2	29.8	24.7	18.9
WSP630-5	5	4"/6"	5.50	7.50	678	3"	136	18.5		57.4	56.2	54.1	51.2	47.4	42.7	37.3	30.9	23.6
WSP630-6	6	4"/6"	7.50	10.00	761	3"	136	21.0		68.9	67.4	64.9	61.4	56.8	51.3	44.7	37.1	28.4
WSP630-7	7	6"	7.50	10.00	850	3"	136	25.5		80.0	78.2	75.3	71.2	65.9	59.5	51.8	42.9	32.8
WSP630-8	8	6"	9.30	12.50	933	3"	136	28.0		89.6	88.0	85.2	81.0	75.4	68.4	60.0	50.2	38.8
WSP630-9	9	6"	9.30	12.50	1016	3"	136	30.5		103.3	98.3	93.1	87.9	82.6	76.8	68.5	57.8	44.4
WSP630-10	10	6"	11.00	15.00	1099	3"	136	33.5		112.5	109.9	105.9	100.3	93.2	84.6	74.3	62.4	48.7
WSP630-11	11	6"	11.00	15.00	1182	3"	136	36.0		124.0	121.0	116.5	110.3	102.4	92.9	81.6	68.5	53.4
WSP630-12	12	6"	13.00	17.50	1265	3"	136	39.0		135.0	131.8	126.8	120.1	111.6	101.3	89.1	74.9	58.5
WSP630-13	13	6"	15.00	20.00	1348	3"	136	41.5		147.0	141.8	135.6	128.3	120.0	110.8	98.6	83.5	64.9
WSP630-14	14	6"	15.00	20.00	1431	3"	136	44.5		158.4	153.6	147.3	139.6	130.4	119.7	106.1	89.3	68.9
WSP630-15	15	6"	15.00	20.00	1514	3"	136	47.0		170.9	165.0	157.8	149.1	138.9	127.8	113.3	95.2	72.8
WSP630-17	17	6"	18.50	25.00	1680	3"	136	52.5		192.9	186.0	178.0	168.8	158.3	145.6	129.3	109.1	82.5
WSP630-18	18	6"	22.00	30.00	1763	3"	136	55.0		202.7	197.9	191.6	183.7	174.3	162.2	145.1	121.9	91.1
WSP630-21	21	6"	22.00	30.00	2012	3"	136	64.0		240.0	229.2	218.1	206.7	195.1	179.5	159.6	134.8	104.0
WSP630-22	22	6"	22.00	30.00	2095	3"	136	67.0		252.9	241.8	230.0	217.5	204.2	187.7	166.9	141.2	109.6
WSP630-23	23	6"	26.00	35.00	2178	3"	136	69.5		264.8	253.2	240.8	227.6	213.5	196.3	174.6	147.8	114.5
WSP630-26	26	6"	30.00	40.00	2427	3"	136	78.0		297.0	285.3	271.8	256.2	238.5	219.6	196.1	166.7	129.8
WSP630-28	28	6"	30.00	40.00	2593	3"	136	84.0		315.0	303.6	290.0	274.2	256.0	234.6	208.5	176.5	136.8
WSP630-30	30	6"	30.00	40.00	2759	3"	136	89.5		332.0	321.4	308.1	292.0	271.4	247.1	218.2	184.0	142.9
WSP630-31	31	6"	37.00	50.00	2842	3"	136	92.0		344.0	333.5	320.2	303.8	284.0	259.9	231.0	191.4	148.5
WSP630-32	32	6"	37.00	50.00	2925	3"	136	95.0		363.6	349.0	332.9	315.2	295.8	273.6	244.0	204.0	161.6
WSP630-34	34	6"	37.00	50.00	3091	3"	136	100.0		388.0	376.8	362.6	345.2	324.0	299.7	269.0	229.8	177.5

