

Performance/ Performances/ Prestaciones

- Maximum sand quantity in the water/ Max quantite de sable dans l'eau/
Maxima cantidad de arena en el agua - 200 g/m3
- Water temperature up to/ Temperature de l'eau jusqu' a/ Temperature del agua hasta - 60 degree Celcius
 - Connection/ Connexion/ Acoplamiento - NEMA Standards
 - Impeller/ Roues/ Rodete - mixed flow/ helicocentrifuges/ semi axiales
- Installation/ Instalacion - horizontal and vertical/ horizontale and verticale

Type Tipo	N. Stages N. Etage N. Etapas	Motor/ Moteur			Pump/ Pompes/ Bombas				Q m3/h l/min	Delivery/ Debit/ Caudal									
		Type Tipo	KW	HP	A (mm)	DN (RPT or NPT)	B (mm)	Kg		0 0	10 166.6	20 333	30 500	40 666	50 833	60 1000	70 1166	80 1333	90 1500
WSP877-1	1	6"	5.50	7.50	451	5"	187	15.5	Head/ Hauteurman/ Alturaman H m	21.0	20.7	20.0	19.0	18.2	17.1	15.7	14.1	12.2	10.0
WSP877-2	2	6"	7.50	10.00	579	5"	187	21.0		41.0	40.5	38.8	36.0	33.6	30.9	28.0	24.9	21.5	17.9
WSP877-3	3	6"	11.00	15.00	708	5"	187	27.0		61.0	60.0	58.0	55.0	51.3	47.3	43.0	38.3	33.3	28.0
WSP877-4	4	6"	15.00	20.00	836	5"	187	33.0		81.0	80.0	77.7	74.0	68.7	63.4	58.0	52.5	47.0	39.4
WSP877-5	5	6"	18.50	25.00	964	5"	187	39.0		101.0	100.0	97.0	92.0	86.0	79.5	72.5	66.3	58.0	47.5
WSP877-6	6	6"	22.00	30.00	1092	5"	187	45.0		120.0	119.9	117.0	110.0	102.5	94.0	86.6	78.0	68.1	57.0
WSP877-7	7	6"	26.00	35.00	1220	5"	187	51.0		140.0	139.6	136.5	127.8	119.0	110.2	101.4	92.5	81.1	66.4
WSP877-8	8	6"/ 8"	30.00	40.00	1349	5"	187	57.0		160.0	160.5	156.5	147.7	137.3	126.7	116.0	105.1	94.0	77.8
WSP877-9A	9	6"/ 8"	37.00	50.00	1477	5"	187	63.0		179.0	178.5	174.0	165.3	152.0	140.0	128.5	117.5	104.0	85.8
WSP877-10	10	6"/ 8"	37.00	50.00	1605	5"	187	69.0		199.6	198.9	194.1	185.0	171.0	157.7	145.0	133.0	116.9	96.2
WSP877-11A	11	8"	45.00	60.00	1775	5"	187	77.0		219.0	219.1	214.0	203.3	186.0	171.7	158.0	145.0	128.0	105.3
WSP877-12	12	8"	59.00	75.00	1903	5"	187	83.0		242.0	242.0	236.8	226.0	209.1	193.0	177.6	163.0	144.9	120.8
WSP877-13	13	8"	55.00	75.00	2132	5"	187	90.0		262.0	262.7	257.4	245.5	227.1	209.8	193.8	177.0	156.4	130.3
WSP877-14	14	8"	55.00	75.00	2160	5"	187	95.0		282.0	283.4	278.0	265.0	245.0	226.7	210.0	191.1	168.0	139.8
WSP877-15	15	8"	63.00	85.00	2288	5"	187	101.0		302.0	304.5	298.0	281.0	261.2	242.0	223.2	205.0	182.1	151.9
WSP877-16	16	8"	63.00	85.00	2416	5"	187	107.0		322.0	324.2	317.5	300.5	279.8	259.2	238.6	218.1	193.7	162.0
WSP877-17	17	8"	75.00	100.00	2544	5"	187	113.0		342.0	343.8	337.0	320.0	298.4	276.4	254.0	231.2	205.2	172.0
WSP877-18A	18	8"	75.00	100.00	2673	5"	187	119.0		362.5	364.4	357.2	339.0	316.3	292.7	268.0	245.1	217.4	181.9
WSP877-19	19	8"	75.00	100.00	2801	5"	187	125.0		383.0	385.0	377.4	358.0	334.3	309.0	282.0	258.9	229.6	191.8
WSP877-20	20	8"	75.00	100.00	2929	5"	187	135.5		402.0	403.2	395.0	375.0	348.1	322.0	296.6	272.0	239.9	200.0

