

Performance/ Performances/ Prestaciones

- Maximum sand quantity in the water/ Max quantite de sable dans l'eau/
Maxima cantidad de arena en el agua - 200 g/m3
- Water temperature up to/ Temperature de l'eau jusqu' a/ Temperature del agua hasta - 60 degree Celcius
 - Connection/ Connexion/ Acoplamiento - NEMA Standards
 - Impeller/ Roues/ Rodete - mixed flow/ helicocentrifuges/ semi axiales
- Installation/ Instalacion - horizontal and vertical/ horizontale and verticale

Type Tipo	N. Stages N. Etage N. Etapas	Motor/ Moteur		Pump/ Pompes/ Bombas			Q m3/h l/min	Delivery/ Debit/ Caudal								
		Type Tipo	KW	HP	A (mm)	DN (RPT or NPT)		B (mm)	Kg	0 0	5 83.3	10 166.6	15 250	20 333	25 416.6	30 500
WSP6 20-5	5	4"	3.00	4.00	546	2.5"	136	14.0	Head/ Hauteurman/ Alturaman H m	48.9	48.3	45.2	39.6	31.5	20.9	7.7
WSP6 20-6	6	4"	4.00	5.50	606	2.5"	136	16.5		58.7	57.9	54.2	47.5	37.9	25.1	9.2
WSP6 20-7	7	4"	4.00	5.50	666	2.5"	136	18.0		68.5	67.9	63.7	56.1	44.8	29.8	10.8
WSP6 20-8	8	4"/ 6"	5.50	7.50	726	2.5"	136	20.0		78.3	77.0	72.0	63.4	50.9	34.4	13.6
WSP6 20-9	9	4"/ 6"	7.50	10.00	786	2.5"	136	22.0		88.1	86.5	81.0	71.3	57.4	38.9	15.7
WSP6 20-10	10	4"/ 6"	7.50	10.00	846	2.5"	136	24.0		97.2	95.5	89.4	78.7	63.3	42.7	16.6
WSP6 20-11	11	6"	7.50	10.00	912	2.5"	136	27.0		105.9	104.6	98.4	87.1	70.5	48.1	19.2
WSP6 20-12	12	6"	7.50	10.00	972	2.5"	136	29.0		115.7	113.9	106.9	94.6	76.5	52.2	20.8
WSP6 20-13	13	6"	7.50	10.00	1032	2.5"	136	31.0		125.0	123.2	115.8	102.5	83.1	56.7	22.3
WSP6 20-14	14	6"	9.30	12.50	1092	2.5"	136	33.0		134.8	132.6	124.6	110.4	89.6	61.3	24.1
WSP6 20-15	15	6"	9.30	12.50	1152	2.5"	136	35.0		146.9	142.2	132.8	118.6	96.3	65.5	24.4
WSP6 20-17	17	6"	9.30	12.50	1272	2.5"	136	39.0		166.4	158.6	150.0	136.5	112.2	74.2	26.2
WSP6 20-18	18	6"	11.00	15.00	1332	2.5"	136	41.0		176.2	168.5	157.0	141.7	117.5	78.0	28.0
WSP6 20-19	19	6"	11.00	15.00	1392	2.5"	136	43.0		186.0	177.8	167.4	152.5	125.6	82.7	29.3
WSP6 20-20	20	6"	11.00	15.00	1452	2.5"	136	45.0		195.8	187.4	175.6	158.8	129.8	84.6	30.8
WSP6 20-21	21	6"	13.00	17.50	1512	2.5"	136	47.0		205.6	196.7	184.8	166.3	136.4	91.1	32.3
WSP6 20-23	23	6"	15.00	20.00	1632	2.5"	136	51.0		224.0	211.5	199.9	183.0	152.0	100.0	36.0
WSP6 20-24	24	6"	15.00	20.00	1692	2.5"	136	53.5		235.0	223.2	210.4	191.7	158.6	103.8	39.2
WSP6 20-26	26	6"	15.00	20.00	1812	2.5"	136	57.5		254.5	241.8	227.8	207.5	171.9	111.8	42.3
WSP6 20-28	28	6"	18.50	25.00	1932	2.5"	136	61.5		274.1	258.8	243.3	222.4	185.1	120.0	44.3
WSP6 20-31	31	6"	18.50	25.00	2112	2.5"	136	67.5		303.5	287.3	269.4	245.7	204.9	133.0	47.7
WSP6 20-33	33	6"	18.50	25.00	2232	2.5"	136	70.5		323.1	306.5	286.8	261.2	218.1	141.9	50.8
WSP6 20-35	35	6"	22.00	30.00	2352	2.5"	136	75.5		342.7	324.9	305.3	277.3	231.3	150.3	53.9
WSP6 20-38	38	6"	22.00	30.00	2532	2.5"	136	81.0		372.0	352.5	330.2	300.1	251.2	163.0	58.5
WSP6 20-40	40	6"	22.00	30.00	2653	2.5"	136	85.5		395.0	374.4	351.0	317.7	266.0	177.0	61.6
WSP6 20-43	43	6"	26.00	35.00	2832	2.5"	136	91.0		421.0	400.3	372.8	337.9	282.2	187.1	66.2
WSP6 20-46	46	6"	26.00	35.00	3012	2.5"	136	97.0		450.8	425.4	395.5	355.4	296.5	197.3	71.3

