

Motor Single phase 50 Hz - 2900 rpm				Technical Data		Dimensions / weights	
TYPE	POWER		A (n)	Axial Thrust (N)	Cable lenght m	L mm	W Kg
	HP	KW	230 V				
WSM 4-05M	0,5	0,37	3,5	1500 N	1,5	317	7
WSM 4-08M	0,8	0,55	4,9	1500 N		337	8
WSM 4-10M	1,0	0,75	6,5	1500 N		362	10
WSM 4-15M	1,5	1,10	9,4	2500 N		392	12
WSM 4-20M	2,0	1,50	11,5	2500 N		422	13
WSM 4-30M	3,0	2,2	14,7	2500 N		467	15

Motor Three phase 50 Hz - 2900 rpm				Technical Data		Dimensions / weights	
Tipo-Type	POWER		A (n)	Axial Thrust (N)	Cable lenght m	L mm	W Kg
	HP	KW	230 V				
WSM 4-05	0,75	0,55	2,2	1500 N	1,5	317	8
WSM 4-10	1,0	0,75	2,2	1500 N		337	10
WSM 4-15	1,5	1,1	3,0	2500 N		362	12
WSM 4-20	2,0	1,5	4,0	2500 N		392	13
WSM 4-30	3,0	2,2	5,7	2500 N	2,5	452	15
WSM 4-40	4,0	3,0	7,4	2500 N		557	19
WSM 4-55	5,5	4,0	10,0	4500 N		597	22
WSM 4-75	7,5	5,5	13,5	4500 N		698	27
WSM 4-100	10,0	7,5	18,0	4500 N		818	32

